

## **Jarke® Button-On Cantilever Racks**



## **STANDARD FEATURES & BENEFITS**

- Button-On lets you load up to 2,000 lbs. at one time with a lift truck or manually
- Provides an adjustable unit with as little as two columns or assembles into a continuous system for growth.
- Arms "button" into position and adjust on 4" centers.
- 700 lbs. to 1,000 lbs. capacity per arm.
- Column capacity 12,000 lbs. per column per side.
- Unique inclined arm with 18° slope, buttons in place. Ideal for storing pipe, tubing, lumber and bar stock.
- Available in starter and add-on units.

## **AVAILABLE STYLES**

More Sizes and Options Are Available. Contact a SPG Product Specialist for a Free Solutions Consultation:

customerservice@spgusa.com

877.503.4SPG (4774)

|                    |              | Capacity |             | No.  | Brace | Capacity |           |        | No.  | Add-On |        |
|--------------------|--------------|----------|-------------|------|-------|----------|-----------|--------|------|--------|--------|
| Ht.                | Arm          | Per Arm  | Base Length | Of   | Set   | Per Unit | Starter   | Wt.    | Of   | Model  | Wt.    |
| (Ft.)              | Length       | (Lbs.)   | (In.)       | Arms | Width | (Lbs.)   | Model No. | (Lbs.) | Arms | No.    | (Lbs.) |
| Single Column Unit |              |          |             |      |       |          |           |        |      |        |        |
| 7                  | 12" inclined | 1,000    | 26 1/2      | 12   | 6'    | 12,000   | CR-1      | 314    | 6    | CR-1A  | 182    |
| 7                  | 12" straight | 1,000    | 26 1/2      | 12   | 6'    | 12,000   | CR-2      | 314    | 6    | CR-2A  | 182    |
| 7                  | 16" inclined | 1,000    | 26 1/2      | 12   | 6'    | 12,000   | CR-5      | 332    | 6    | CR-5A  | 191    |
| 7                  | 16" straight | 1,000    | 26 1/2      | 12   | 6'    | 12,000   | CR-6      | 332    | 6    | CR-6A  | 191    |
| 10                 | 20" straight | 850      | 34 1/2      | 20   | 6'    | 17,000   | CR-9      | 445    | 10   | CR-9A  | 257    |
| 10                 | 24" straight | 700      | 34 1/2      | 20   | 6'    | 14,000   | CR-10     | 485    | 10   | CR-10A | 277    |
| Double Column Unit |              |          |             |      |       |          |           |        |      |        |        |
| 7                  | 12" inclined | 1,000    | 45          | 24   | 6'    | 24,000   | CR-3      | 406    | 12   | CR-3A  | 228    |
| 7                  | 16" inclined | 1,000    | 45          | 24   | 6'    | 24,000   | CR-7      | 442    | 12   | CR-7A  | 246    |
| 7                  | 16" straight | 1,000    | 45          | 24   | 6'    | 24,000   | CR-8      | 442    | 12   | CR-8A  | 246    |
| 10                 | 20" straight | 850      | 61          | 40   | 6'    | 34,000   | CR-11     | 687    | 20   | CR-11A | 371    |

