



## STANDARD FEATURES & BENEFITS

- Aluminum construction offers higher load ratings — so larger loads can be supported across a longer span of shelving
- Aluminum shelving is ideal in hot or caustic applications that might damage the coating of wire shelving
- All welded aluminum shelving ships set up
- Overall height is 60" for 2 and 3-shelf units and 72" for 4-shelf unit
- Mitered top for extra strength
- Choose from 3 types of shelves

## AVAILABLE STYLES

T-Bar Shelves  
Channel Shelves  
Tubular Shelves

**\*All Shelf Size and Finish Combinations May Not Be Available. Please Contact SPG for Lead Time and Availability.**

Kelmax® T-Bar Shelving Unit	Tiers	L X W		Weight	
		(in.)	(mm)	(lbs)	(kg)
24- inch Wide Shelves					
4H0644	3	48 x 24 x 60	1219 x 610 x 1524	51	23
4H0649	4	60 x 24 x 72	1524 x 610 x 1829	79	36
4H0647	3	60 x 24 x 60	1524 x 610 x 1524	61	28
4H0645	4	48 x 24 x 72	1219 x 610 x 1829	66	30



## Kelmax® Aluminum Fixed Shelving

Kelmax® Tubular Shelving Unit	Tiers	L X W		Weight	
		(in.)	(mm)	(lbs)	(kg)
24- inch Wide Shelves					
4H6350	3	48 x 24 x 60	1219 x 610 x 1524	51	23

Kelmax® Channel Shelving Unit	Tiers	L X W		Weight	
		(in.)	(mm)	(lbs)	(kg)
24- inch Wide Shelves					
4H0495	3	48 x 24 x 60	1219 x 610 x 1524	51	23
4H0540	4	60 x 24 x 72	1524 x 610 x 1829	79	36

Kelmax® Tubular Shelving Unit	Tiers	L X W		Weight	
		(in.)	(mm)	(lbs)	(kg)
20- inch Wide Shelves					
4H0594	4	48 x 20 x 72	1219 x 508 x 1829	59	27
4H0609	3	60 x 20 x 60	1524 x 508 x 1524	54	24

Kelmax® T-Bar Shelving Unit	Tiers	L X W		Weight	
		(in.)	(mm)	(lbs)	(kg)
20- inch Wide Shelves					
4H7058	3	60 x 20 x 60	1524 x 508 x 1524	54	24
4H0646	4	60 x 20 x 72	1524 x 508 x 1829	70	32

**\*All Shelf Size and Finish Combinations  
May Not Be Available. Please Contact SPG  
for Lead Time and Availability.**

